



## PRODUCT INFORMATION

## Cuttable Heat Transfer Vinyl

- Flake (Normal, Neon, White, Holo, Rainbow)

Polyester glitter treated thermal transfer film designed for cad-cutting application

### AVAILABLE COLORS

Flake(FK-01~FK-55): Brilliant sparkle, shiny colors

### SPECIFICATION

- Thickness(excluding 100micron PET liner): 320micron
- Size: 0.5m(20") \* 25m(27.34yd) or 50m(54.68yd) per roll

### PACKING

Individual paper box per roll plus pallet packing

- Volume :
  - 0.5m \* 50m : 195\*195\*520mm, 12kg
  - 0.5m \* 25m : 165\*165\*520mm, 6kg

### TRANSFER CONDITION

- Temperature: 150°C(302°F)
- Pressing time: 8~10 seconds
- Pressure: about 30kg
- Peeling condition: **Cool peel**

### HOW TO USE

1. Cut the film in mirror image
2. Weed the useless parts
3. Place the film on the garment
4. Heat apply
5. Remove application tape when it is hot

### RECOMMENDED FABRICS

100% cotton, 100% polyester  
Poly/cotton blends, Acrylics

*All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.*

LAST UPDATED 06/2017

### MINSEO COATING FELX CO., LTD.

ADDRESS : 382 Jeongmun-ro, Wollong-myeon, Paju-si, Gyeonggi-do, Republic of Korea, 10947  
TEL: 82 31 991 4301 FAX: 82 31 991 4302 EMAIL: info@minseo.kr URL: www.minseo.kr